

## LED15WT8 8XX COMP



<b>Model Numbers:</b>	<b>#943 - LED15WT8 840 COMP</b> <b>#944 - LED15WT8 850 COMP</b>
<b>Electronic Ballast Compatibility:</b>	Instant Start Program Start Rapid Start (Electronic) Emergency Ballast
<b>Rated Power (W):</b>	15 Watts
<b>Colour Temperatures Available:</b>	4000K / 5000K
<b>Power Factor:</b>	0.9
<b>Total Harmonic Distortion (THD):</b>	20%
<b>Ignition Time:</b>	≤ 1.0 second
<b>Light Output:</b>	2200lm
<b>Efficacy:</b>	146 lm/W
<b>Colour Rendering Index (CRI):</b>	≥ 80
<b>Rated Life:</b>	50,000 Hrs.
<b>Nominal Length:</b>	4 Feet
<b>Diffuser Material:</b>	Glass (Non-Yellowing, Rigid)
<b>Beam Angle:</b>	230° (Extra Wide Beam Angle)
<b>Certifications:</b>	DLC / cULus / NSF
<b>Carton Quantity:</b>	10 pieces / box

<b>Ballast Factor</b>	<b>.78 BF</b>	<b>.88 BF</b>	<b>1.18 BF</b>
<b>Lamp Wattage (lamp only)</b>	13.4 W	15 W	20.1 W
<b>System Wattage (including ballast)</b>	15.8 W	17.5 W	24.1 W
<b>Initial Lumens</b>	1980 lm	2200 lm	2840 lm