



LED 6-inch Downlight Fire-Rated



SKU / Model No:	#1124 - LED DP6-FR-5CCT
Factory Model:	FR-LED-6-S15-5CCT**-PL
Wattage:	15W
Selectable Colour Temperature:	2700K / 3000K / 3500K / 4000K / 5000K
Light Output:	1200 lm
Voltage:	120VAC
Beam Angle:	110°
L70 Rated Life:	50,000 Hrs.
Base Type:	Hardwire
Energy Efficiency:	80 lm/W
Dimmable:	Yes - TRIAC
CRI:	≥ 80
Diameter:	6-15/16" / 176 mm
Height:	1-5/16" / 34 mm
Driver Dimensions:	3-5/8" L x 3-7/8" W x 1-5/16" H
2-HR Fire Rating Compliance	UL 263, ASTM E119, CAN ULC S101
Certifications:	2-Hour Fire-Rated, Wet Location, Airtight
Environmental Rating:	Wet Location, Type IC
Operating Temperature:	-20°C to 45°C
Hole Cutout Size:	6.25 inches / 158 mm
Carton Quantity:	18 pieces per Carton
Warranty:	5 Years



2 HOUR FIRE RATING
Tested to comply with UL 263,
ASTM E119 & CAN ULC S101



Intertek

