



LED COB RIBBON LIGHT SYSTEM



24VDC

COB LED Ribbon Lights - 8MM - IP20

Continuous Lighting - No Dots - No More Dark Corners

Cut Anywhere - Rejoin Anywhere - Super Easy Connectors - No Waste

Fully Dimmable

Optional Aluminum Channel

Dimming: Yes when used with dimmable LED Driver.

Mounting: Pre-affixed 3M double stick mounting tape.

Electrical: Power consumption of 3.35W per foot.

Maximum Length: 39.5 feet in Series

Packaging: 20 feet per Reel

SKU #	LED RIBBON Model Number	Length	Watts per Foot	LED's per Foot	Lumens per Foot	LED Life (Hrs)
1009	LED RL-COB-30K-20FT	20 FT	3.35W	160.9	274.3 lm	30,000 Hrs
1138	LED RL-COB-40K-20FT	20 FT	3.35W	160.9	310.9 lm	30,000 Hrs




LED COB RIBBON LIGHT SYSTEM



RL-COB-6LE




RL-COB-12EX




RL-COB-RWC




RL-COB-20FTWires



RL-COB-IC



RL-COB-LC



RL-COB-TC









IFP03-1M

SKU #	Model	Description: LED Ribbon Accessories
1145	RL-COB-6LE	6" Lead for COB Ribbon (input cable)
1146	RL-COB-12EX	12" Extension Cord for COB Ribbon
1144	RL-COB-RWC	COB Ribbon to Wire Connector (custom input / output)
1147	RL-COB-20FTWires	COB Ribbon 20FT Wires (20AWG)
1143	RL-COB-IC	COB Ribbon I or Straight Connector
1142	RL-COB-LC	COB Ribbon L-Connector
1139	RL-COB-TC	COB Ribbon T-Connector
1153	IFP09-1M	Aluminum Channel - 1 Meter Length



LED COB RIBBON LIGHT SYSTEM

24VDC LED DRIVERS - HARDWARE

SKU #	Model	24VDC LED DRIVERS - DIMMABLE 120V Input
	1148 PS40W-24V Max Run: 11.4FT	Output 38.4W 24VDC 1.6A Hardwire Built-in Enclosure - cETLus Input 120VAC Dimmable. Class II. Electronic, IP20
	1149 PS60W-24V Max Run: 17.9 FT	Output 60W 24VDC 2.5A Hardwire Built-in Enclosure - cETLus Input 120VAC Dimmable. Class II Electronic, IP20
	1150 PS80W-24V Max Run: 23.5FT	Output 79W 12VDC 3.3A Hardwire Built-in Enclosure - cETLus Input 120VAC Dimmable. Class II. Electronic, IP20
	1151 PS100W-24V Max Run 30FT	Output 100.8W 24VDC 4.2A Hardwire Built-in Enclosure - cETLus Input 120VAC Dimmable. Class II Electronic, IP20
	1152 PS150W-24V Max Run: 44.7FT in Parallel Only	Output 150W 24VDC 6.25A Hardwire - cELTus 30cm / 11.5" Pigtails - 18/3 Input, 16/2 Output Input 120VAC Dimmable. Electronic, IP20
24VDC LED DRIVERS - NON-DIMMABLE 200V-240V Input or 100V-120V		
	1103 PS100W-MC-24V Max Run: 32FT in Parallel Only	Output 108W 24VDC 4.5A. Hardwire - cRUus Screw Terminals. Input 100V-120VAC 2.5A or Input 200V-240VAC 1.5A Switch-Mode. Metal Chassis. Electronic.