



LED12WT8-HY-XXK



T8 HYBRID Lamp

Both Ballast Compatible & Ballast Bypass Operation

| | |
|-----------------------------------|--|
| Model Numbers: | #1014 - LED12WT8-HY 40K #1015 - LED12WT8-HY 50K |
| Operation: | 1 - Ballast Compatible 2 - Ballast Bypass (Double Ended) |
| Rated Power (W): | 14 Watts |
| Colour Temperatures Available: | 4000K , 5000K |
| Power Factor: | 0.99 |
| Total Harmonic Distortion (THD): | 16% |
| Socket Compatibility: | Shunted & Non-Shunted |
| Light Output: | 1800 lm |
| Efficacy: | 128 lm/W |
| Colour Rendering Index (CRI): | ≥ 80 |
| Rated Life: | 50,000 Hrs. |
| Nominal Length: | 4 Feet |
| Diffuser Material: | Glass (Non-Yellowing, Rigid) |
| Beam Angle: | 150° |
| Dimming Compatibility and Rangel: | Continuous Dimming to 10% or below |
| Wired Communication Protocol: | TypeA: Dimmable depending on ballast compatibility TypeB: Phase Cut |
| Certifications: | cUL / cUL Classified / NSF / DLC 5.1 |
| Classification Type: | cUL Type A & Type B |
| Operating Voltage: | 120VAC - 277VAC |
| Carton Quantity: | 25 pieces per box (Must be sold in Carton Quantity) |
| Limited Warranty: | 5 Years |